

Low Capacitance TVS - 500W

TVS

500 W	Min. Breakdown Voltage @ Test Current		Stand-off Voltage	Max. Reverse Leakage @ V_{WM}	Max. Clamping Voltage @ $I_{PP}=5.0A$	Max. Peak Pulse Current @ 10/1000 μ s	Max. Junction Capacitance @ 0 V	Peak Inverse Blocking Voltage	Package	Outline (Typ. in Inches)
	Part No.	$V_{(BR)}(V)$								
SAC5.0	7.60	1.0	5.0	300.0	10.0	44.0	50	100	4000	
SAC6.0	7.90	1.0	6.0	300.0	11.2	41.0	50	100		
SAC7.0	8.33	1.0	7.0	300.0	12.6	38.0	50	100		
SAC8.0	8.89	1.0	8.0	100.0	13.4	36.0	50	100		
SAC8.5	9.44	1.0	8.5	50.0	14.0	34.0	50	100		
SAC10	11.10	1.0	10.0	5.0	16.3	29.0	50	100		
SAC12	13.30	1.0	12.0	5.0	19.0	25.0	50	100		
SAC15	16.70	1.0	15.0	5.0	23.6	20.0	50	100		
SAC18	20.00	1.0	18.0	5.0	28.8	15.0	50	100		
SAC22	24.40	1.0	22.0	5.0	35.4	14.0	50	100		
SAC26	28.90	1.0	26.0	5.0	42.3	11.1	50	100		
SAC30	33.30	1.0	30.0	5.0	48.6	10.0	50	100		
SAC36	40.00	1.0	36.0	5.0	60.0	8.6	50	100		
SAC45	50.00	1.0	45.0	5.0	77.0	6.8	50	200		
SAC50	55.50	1.0	50.0	5.0	88.0	5.8	50	200		