

T02 Series

0.100" Centerline Dual-In-Line IC Socket

T02 Series/IC SOCKET

Specifications	Feature
Storage Temperature: -20 ~ 80°C	Insulator: Thermoplastic (UL 94V-0)
Operating Temperature: -65 ~ 150°C	Contact: Phosphor Bronze, 150u" Tin plating over 30u" to 50u" Nickel
Contact Resistance: 20 mΩ Max.(initial)	Dual contacts open frame structure
Insulation Resistance: 1000 MΩ Min.	Stackable end-to-end and side-to-side
Dielectric withstanding voltage: AC 500V per minute	Polarization mark

RoHS Compliant

T02 Series/IC SOCKET

Part Number	No. of Contacts	Spacing in inch(mm)	Dimensions in inch (mm)			Contact Plating	Diagram
			A	B	C		
T02-06	6	0.300(7.62)	0.300(7.62)	0.300(7.62)	0.400(10.16)	Tin	
T02-08	8		0.400(10.16)	0.300(7.62)	0.400(10.16)		
T02-14	14		0.700(17.78)	0.300(7.62)	0.400(10.16)		
T02-16	16		0.800(20.32)	0.300(7.62)	0.400(10.16)		
T02-18	18		0.900(22.86)	0.300(7.62)	0.400(10.16)		
T02-20	20		1.00(25.40)	0.300(7.62)	0.400(10.16)		
T02-22S	22S		1.10(27.94)	0.300(7.62)	0.400(10.16)		
T02-24S	24S		1.20(30.48)	0.300(7.62)	0.400(10.16)		
T02-28S	28S		1.40(35.56)	0.300(7.62)	0.400(10.16)		
T02-24	24	0.600(15.24)	1.20(30.48)	0.600(15.24)	0.700(17.78)		
T02-28	28		1.40(35.56)	0.600(15.24)	0.700(17.78)		
T02-32	32		1.60(40.64)	0.600(15.24)	0.700(17.78)		
T02-40	40		2.00(50.80)	0.600(15.24)	0.700(17.78)		
T02-42	42		2.10(53.34)	0.600(15.24)	0.700(17.78)		
T02-48	48		2.40(60.96)	0.600(15.24)	0.700(17.78)		
T02-64S	64S		3.20(81.28)	0.600(15.24)	0.700(17.78)		