


SMD Zener Diodes (Two Terminals) - 1.5W

1.5 W	Marking Code	Nominal Zener Voltage @ I_{ZT}			Test Current	Max. Zener Impedance (Ω)			Maximum Reverse Leakage Current I_R @ V_R		Package	Outline (Typ. in Inches)
		Nom.	Min.	Max.		Z_{ZT} @ I_{ZT}	Z_{ZK} @ I_{ZK}	I_{ZK} (mA)	I_R (μ A)	V_R (V)		
Part No.		V_Z (V)	V_Z (V)	V_Z (V)	I_{ZT} (mA)						7" / 13" Reel	
Z1.5SMA5921B	921A	6.8	6.46	7.14	55.1	3	200	1.00	5.0	5.20	1800/ 7500	
Z1.5SMA5922B	922A	7.5	7.13	7.88	50.0	3	400	0.50	5.0	6.00		
Z1.5SMA5923B	923A	8.2	7.79	8.61	45.7	4	400	0.50	5.0	6.50		
Z1.5SMA5924B	924A	9.1	8.65	9.56	41.2	4	500	0.50	5.0	7.00		
Z1.5SMA5925B	925A	10	9.50	10.50	37.5	5	500	0.25	5.0	8.00		
Z1.5SMA5926B	926A	11	10.45	11.55	34.1	6	550	0.25	1.0	8.40		
Z1.5SMA5927B	927A	12	11.40	12.60	31.2	7	550	0.25	1.0	9.10		
Z1.5SMA5928B	928A	13	12.35	13.65	28.8	7	550	0.25	1.0	9.90		
Z1.5SMA5929B	929A	15	14.25	15.75	25.0	9	600	0.25	1.0	11.40		
Z1.5SMA5930B	930A	16	15.20	16.80	23.4	10	600	0.25	1.0	12.20		
Z1.5SMA5931B	931A	18	17.10	18.90	20.8	12	650	0.25	1.0	13.70		
Z1.5SMA5932B	932A	20	19.00	21.00	18.7	14	650	0.25	1.0	15.20		
Z1.5SMA5933B	933A	22	20.90	23.10	17.0	18	650	0.25	1.0	16.70		
Z1.5SMA5934B	934A	24	22.80	25.20	15.6	19	700	0.25	1.0	18.20		
Z1.5SMA5935B	935A	27	25.65	28.35	13.9	23	700	0.25	1.0	20.20		
Z1.5SMA5936B	936A	30	28.50	31.50	12.5	26	750	0.25	1.0	22.80		
Z1.5SMA5937B	937A	33	31.35	34.65	11.4	33	800	0.25	1.0	25.10		
Z1.5SMA5938B	938A	36	34.20	37.80	10.4	38	850	0.25	1.0	27.40		
Z1.5SMA5939B	939A	39	37.05	40.95	9.6	45	900	0.25	1.0	29.70		
Z1.5SMA5940B	940A	43	40.85	45.15	8.7	53	950	0.25	1.0	32.70		
Z1.5SMA5941B	941A	47	44.65	49.35	8.0	67	1000	0.25	1.0	35.80		
Z1.5SMA5942B	942A	51	48.45	53.55	7.3	70	1100	0.25	1.0	38.80		
Z1.5SMA5943B	943A	56	53.20	58.80	6.7	86	1300	0.25	1.0	42.60		
Z1.5SMA5944B	944A	62	58.90	65.10	6.0	100	1500	0.25	1.0	47.10		
Z1.5SMA5945B	945A	68	64.60	71.40	5.5	120	1700	0.25	1.0	51.70		

SMA

