


SMD Zener Diodes (Two Terminals) - 1.5W

1.5 W	Marking Code	Nominal Zener Voltage @ I_{ZT}			Test Current	Max. Zener Impedance (Ω)			Maximum Reverse Leakage Current I_R @ V_R		Package	Outline (Typ. in Inches)
		Nom.	Min.	Max.		Z_{ZT} @ I_{ZT}	Z_{ZK} @ I_{ZK}	I_{ZK} (mA)	I_R (μ A)	V_R (V)		
Part No.		V_Z (V)	V_Z (V)	V_Z (V)	I_{ZT} (mA)						7" /13" Reel	
Z1.5SMB5921B	921B	6.8	6.46	7.14	55.1	3	200	1.00	5.0	5.2	750/ 3200	
Z1.5SMB5922B	922B	7.5	7.13	7.88	50.0	3	400	0.50	5.0	6.0		
Z1.5SMB5923B	923B	8.2	7.79	8.61	45.7	4	400	0.50	5.0	6.5		
Z1.5SMB5924B	924B	9.1	8.65	9.56	41.2	4	500	0.50	5.0	7.0		
Z1.5SMB5925B	925B	10	9.50	10.50	37.5	4	500	0.25	5.0	8.0		
Z1.5SMB5926B	926B	11	10.45	11.55	34.1	6	550	0.25	1.0	8.4		
Z1.5SMB5927B	927B	12	11.40	12.60	31.2	7	550	0.25	1.0	9.1		
Z1.5SMB5928B	928B	13	12.35	13.65	28.8	7	550	0.25	1.0	9.9		
Z1.5SMB5929B	929B	15	14.25	15.75	25.0	9	600	0.25	1.0	11.4		
Z1.5SMB5930B	930B	16	15.20	16.80	23.4	10	600	0.25	1.0	12.2		
Z1.5SMB5931B	931B	18	17.10	18.90	20.8	12	650	0.25	1.0	13.7		
Z1.5SMB5932B	932B	20	19.00	21.00	18.7	14	650	0.25	1.0	15.2		
Z1.5SMB5933B	933B	22	20.90	23.10	17.0	18	650	0.25	1.0	16.7		
Z1.5SMB5934B	934B	24	22.80	25.20	15.6	19	700	0.25	1.0	18.2		
Z1.5SMB5935B	935B	27	25.65	28.35	13.9	23	700	0.25	1.0	20.6		
Z1.5SMB5936B	936B	30	28.50	31.50	12.5	26	750	0.25	1.0	22.8		
Z1.5SMB5937B	937B	33	31.35	34.65	11.4	33	800	0.25	1.0	25.1		
Z1.5SMB5938B	938B	36	34.20	37.80	10.4	38	850	0.25	1.0	27.4		
Z1.5SMB5939B	939B	39	37.05	40.95	9.6	45	900	0.25	1.0	29.7		
Z1.5SMB5940B	940B	43	40.85	45.15	8.7	52	950	0.25	1.0	32.7		
Z1.5SMB5941B	941B	47	44.65	49.35	8.0	67	1000	0.25	1.0	35.8		
Z1.5SMB5942B	942B	51	48.45	53.55	7.3	70	1100	0.25	1.0	38.8		