


3.0A Sintered Glass Passivated Super Fast Recovery Rectifier (SGP®)

Features

- Sintered glass passivated (SGP®) rectifier chip
- Low forward voltage, high current capability
- Low leakage current, high surge current capability
- High temperature soldering guaranteed: 260°C/10 seconds
/.0375" (9.5mm) lead length, 5lbs (2.3kg) tension
- RoHS Compliance



DO-201AD



Mechanical Data

Case:	JEDEC DO-201AD molded plastic body
Epoxy:	Plastic package has UL flammability classification 94V-0
Terminals:	Plated axial leads, solderable per MIL-STD-750, Method 2026
Polarity:	Color band denotes cathode end
Weight:	0.04ounces, 1.12 grams

Maximum Ratings and Electrical Characteristics ($T_A=25^\circ\text{C}$ unless noted otherwise)

Symbol	Description	EGP30A	EGP30B	EGP30D	EGP30G	EGP30J	EGP30K	Unit	Conditions
VRRM	Maximum Repetitive Peak Reverse Voltage	50	100	200	400	600	800	V	
VRMS	Maximum RMS Voltage	35	70	140	280	420	560	V	
VDC	Maximum DC Blocking Voltage	50	100	200	400	600	800	V	
IF(AV)	Maximum Average Forward Rectified Current	3.0						A	0.375" (9.5mm) lead length(Fig.1)
IFSM	Peak Forward Surge Current	125				115		A	8.3ms single half sine-wave superimposed on rated load (JEDEC Method)

3.0A Sintered Glass Passivated Super Fast Recovery Rectifier (SGP[®])

EGP30A - EGP30K

Symbol	Description	EGP30A	EGP30B	EGP30D	EGP30G	EGP30J	EGP30K	Unit	Conditions
V _F	Maximum Instantaneous Forward Voltage	0.95			1.25	1.70	2.20	V	I _F =3.0 A
I _R	Maximum DC Reverse Current at Rated DC Blocking Voltage	5						μA	T _A =25° C
		120							T _A =125° C
T _{rr}	Typical Reverse Recovery Time	35						nS	I _F =0.5A, I _R =1A, I _{rr} =0.25A
C _J	Typical Junction Capacitance	35						pF	V _R =4V, f=1MHz
R _{thJA}	Typical Thermal Resistance	20						°C / W	Note
T _J	Operating Temperature range	-55 to +175						° C	
T _{STG}	Storage Temperature Range	-55 to +175							

Note: Thermal resistance from junction to ambient at 0.375" (9.5mm) lead lengths, P.C.B mounted.

Typical Characteristics Curves

Fig.1-Max. Forward Current Derating Curve





Fig.2-Max. Non-Repetitive Forward Surge Current



3.0A Sintered Glass Passivated Super Fast Recovery Rectifier (SGP[®])

EGP30A - EGP30K

Fig.3- Typical Forward Characteristics




Fig.4-Typical Reverse Characteristics






Fig.5- Typical Junction Capacitance



3.0A Sintered Glass Passivated Super Fast Recovery Rectifier (SGP[®])

EGP30A - EGP30K

Dimensions in inches (mm)



DO-201AD

How to contact us:

US HEADQUARTERS

28040 WEST HARRISON PARKWAY, VALENCIA, CA 91355-4162

Tel: (800) TAITRON (800) 824-8766 (661) 257-6060

Fax: (800) TAITFAX (800) 824-8329 (661) 257-6415

Email: taitron@taitroncomponents.com

Http://www.taitroncomponents.com

TAITRON COMPONENTS MEXICO, S.A .DE C.V.

BOULEVARD CENTRAL 5000 INTERIOR 5 PARQUE INDUSTRIAL ATITALAQUIA, HIDALGO C.P.

42970 MEXICO

Tel: +52-55-5560-1519

Fax: +52-55-5560-2190

TAITRON COMPONETS INCORPORATED E REPRESENTAÇÕES DO BRASIL LTDA

RUA DOMINGOS DE MORAIS, 2777, 2.ANDAR, SALA 24 SAÚDE - SÃO PAULO-SP 04035-001 BRAZIL

Tel: +55-11-5574-7949

Fax: +55-11-5572-0052

TAITRON COMPONETS INCORPORATED, SHANGHAI REPRESENTATIVE OFFICE

METROBANK PLAZA, 1160 WEST YAN' AN ROAD, SUITE 1503, SHANGHAI, 200052, CHINA

Tel: +86-21-5424-9942

Fax: +86-21-5424-9931