


3.0A Glass Passivated Ultra Fast Recovery Rectifier

Features

- Glass passivated chip junction
- Low forward voltage drop, high current capability
- Low leakage, high forward surge capability
- High temperature soldering guaranteed: 250°C, 0.375" (9.5mm), lead length for 10 seconds, 5 lbs. (2.3kg) tension
- RoHS Compliance



DO-201AD



Mechanical Data

Case:	JEDEC DO-201AD molded plastic over passivated chip
Epoxy:	Plastic package has UL flammability classification 94V-0
Terminals:	Plated axial leads, solderable per MIL-STD-750, Method 2026
Polarity:	Color band denotes cathode end
Mounting Position:	Any
Weight:	0.04 ounce, 1.1 gram

Maximum Ratings and Electrical Characteristics ($T_A=25^\circ\text{C}$ unless otherwise noted)

Symbol	Description	UF 5400G	UF 5401G	UF 5402G	UF 5403G	UF 5404G	UF 5405G	UF 5406G	UF 5407G	UF 5408G	Unit	Conditions
VRRM	Max. Repetitive Peak Reverse Voltage	50	100	200	300	400	500	600	800	1000	V	
VRMS	Max. RMS Voltage	35	70	140	210	280	350	420	560	700	V	
VDC	Max. DC Blocking Voltage	50	100	200	300	400	500	600	800	1000	V	
IF(AV)	Max. Average Forward Rectified Current	3.0									A	0.375" (9.5mm) lead length at $T_A=55^\circ\text{C}$
IFSM	Peak Forward Surge Current	150									A	8.3ms single half sine-wave superimposed on rated load (JEDEC Method)
VF	Max. Instantaneous Forward Voltage	1.0					1.7				V	IF(AV)=3.0A, Note 1

3.0A Glass Passivated Ultra Fast Recovery Rectifier



UF5400G - UF5408G

Symbol	Description	UF 5400G	UF 5401G	UF 5402G	UF 5403G	UF 5404G	UF 5405G	UF 5406G	UF 5407G	UF 5408G	Unit	Conditions
I _R	Max. DC Reverse Current at Rated DC Blocking Voltage	10									μA	TA=25°C
		75			200							TA=100°C
T _{rr}	Max. Reverse Recovery Time	50			75						nS	T _J =25°C, I _F =0.5A, I _R =1.0A, I _{rr} =0.25A
C _J	Typical Junction Capacitance	45			36						pF	V _R = 4V, f=1MHz
R _{thJA}	Typical Thermal Resistance	20									°C / W	Note 2
R _{thJL}		8.5										
T _J , T _{STG}	Operating Junction and Storage Temperature Range	-55 to +150									°C	

Note: 1. Pulse test: 300μS pulse width, 1% duty cycle.

2. Thermal resistance from junction to lead and from junction to ambient with 0.375" (9.5mm) lead length, both leads attached to heatsink.

Typical Characteristics Curves



3.0A Glass Passivated Ultra Fast Recovery Rectifier

UF5400G - UF5408G

Fig.3-Typical Instantaneous Forward Characteristics




Fig.4-Typical Reverse Characteristics






Fig.5-Typical Junction Capacitance



3.0A Glass Passivated Ultra Fast Recovery Rectifier

UF5400G - UF5408G

Dimensions in inches (mm)



DO-201AD

How to contact us:

US HEADQUARTERS

28040 WEST HARRISON PARKWAY, VALENCIA, CA 91355-4162

Tel: (800) TAITRON (800) 824-8766 (661) 257-6060

Fax: (800) TAITFAX (800) 824-8329 (661) 257-6415

Email: taitron@taitroncomponents.com

Http://www.taitroncomponents.com

TAITRON COMPONENTS MEXICO, S.A .DE C.V.

BOULEVARD CENTRAL 5000 INTERIOR 5 PARQUE INDUSTRIAL ATITALAQUIA, HIDALGO C.P.
42970 MEXICO

Tel: +52-55-5560-1519

Fax: +52-55-5560-2190

TAITRON COMPONENTS INCORPORATED REPRESENTAÇÕES DO BRASIL LTDA

RUA DOMINGOS DE MORAIS, 2777, 2.ANDAR, SALA 24 SAÚDE - SÃO PAULO-SP 04035-001 BRAZIL

Tel: +55-11-5574-7949

Fax: +55-11-5572-0052

TAITRON COMPONENTS INCORPORATED, SHANGHAI REPRESENTATIVE OFFICE

METROBANK PLAZA, 1160 WEST YAN' AN ROAD, SUITE 1503, SHANGHAI, 200052, CHINA

Tel: +86-21-5424-9942

Fax: +86-21-5424-9931