LOT DETAILS

Market Support - Surplus Sales | Lot 24.19 | Total Quantity (PCS): 268,344

Lot Summary

Warehouse	Los Angeles, California	**Categories**	Opto Devices
Number of Items	104	**Total Quantity**	268,344 PCS
Pallet Weight	920.0 lb (417.3 kg)	**Pallet Dimensions**	48.0 x 43.0 x 69.0 in (121.9 x 109.2 x 175.3 cm)
Sales Term	Complete pallet lot; sold as-is; all sales final; no returns.	**Lot**	Lot 24.19

Items

#	Part Number	Brand	Category	Package	Outline	Cartons	Quantity	Datasheet	Description
1	**4N26.300-QT-C**	QT	Optoelectronics	C	DIP-6	1	1,000	4N26.300	Optocouplers,Phototransistor Output,VDE0884,CTR >=20%,IF=80mA,Vceo >=30V,Viso >=5300Vrms,VF=1.2V(Typ.),Vio>=1500V,Vce(Sat) <=0.5V,in DIP-6 PKG
2	**4N36-QT-C**	QT	Optoelectronics	C	DIP-6	1	450	4N36	Optocouplers,Phototransistor Output,CTR >=100%,IF=60mA,Vceo >=30V,Viso >=5300Vrms,Vio=2500V,Vce(Sat) <=0.3V, in DIP-6 PKG.
3	**CNW11AV-2-QT-C**	QT	Optoelectronics	C	DIP-6	1	1,050	CNW11AV-2	Optocouplers/TR Output, CTR >=50%, Vceo >=70V, Viso >=4000Vrms, Typical ton=15us, toff=15us, in DIP-6
4	**CNW139-QT-C**	QT	Optoelectronics	C	DIP-8	1	2,480	CNW139	High Gain Split Optocouplers/Darlington Output, CTR >=500%, Vis >=5000Vrms, Vce(Sat) <=0.4V, Typical ton=1.0us, toff=7.0us, in DIP-8
5	**CNY17-1-QT-C**	QT	Optoelectronics	C	DIP-6	1	3,300	CNY17-1	Optocouplers/TR Output, CTR 40~80%, Vceo >=70V, Viso >=5300Vrms, Vce(Sat) <=0.4V, Typical ton=10us, toff=10us, in DIP-6
6	**CNY17-4-QT-C**	QT	Optoelectronics	C	DIP-6	1	5,250	CNY17-4	Optocouplers/TR Output, CTR 160~320%, Vceo >=70V, Viso >=5300Vrms, Vce(Sat) <=0.4V, Typical ton=10us, toff=10us, in DIP-6
7	**CNY17F-1-QT-C**	QT	Optoelectronics	C	DIP-6	1	4,850	CNY17F-1	Optocouplers/TR Output/GaAs Input, CTR 40~80%, Vceo >=70V, Viso >=5300Vrms, Vce(Sat) <=0.4V, Typical ton=10us, toff=10us, No Base Connection, in DIP-6
8	**EL31-01SURC-EL-C**	EL, EVERLIGHT	Optoelectronics	C	W3	1	1,200	-	3mm Piranha, Super Red LED,AlGaInP, 624nm,1310mlm(Typ.)at 70mA, Water clear, 50 Degree, in Tube Packing
9	**EL31-01URC-EL-C**	EL, EVERLIGHT	Optoelectronics	C	-	1	1,800	-	High Power Piranha, Super Red(GaAlAs, 643nm), Water clear, 50 degree Viewing Angle
10	**EL333HD/TR1-2-R-EL-TR**	EL, EVERLIGHT	Optoelectronics	TR	R5	3	21,000	-	5mm(T-1 3/4) Round,Cut Flange,Bright Red LED,GaP,650nm,1.0(Typ.)at 10mA,60 Degree,in Reel Packing.
11	**EL91-21EC/TR7-EL-T**	EL, EVERLIGHT	Optoelectronics	T	C1008	1	15,000	-	SMD LF Type,1.9 mm Round,G-Bend,Hi-Eff Red LED,GaAsP/GaP, 625nm, 24mcd(Typ.)at 20mA,25 Degree,in Reel Packing.
12	**EL91-21EC/TR9-EL-T**	EL, EVERLIGHT	Optoelectronics	T	C1008	1	16,000	-	SMD LF Type,1.9 mm Round,Y-Bend,Hi-Eff Red LED,GaAsP/GaP 625nm, 24mcd(Typ.)at 20mA,25 Degree,in Reel Packing.
13	**EL91-21GC/TR7-EL-T**	EL, EVERLIGHT	Optoelectronics	T	C1008	1	12,000	-	SMD LF Type,1.9 mm Round,G-Bend,Green LED, GaP, 565nm,21mcd(Typ.)at 20mA,25 Degree,in Reel Packing
14	**ELB1001EWA(K)-EL-C**	EL, EVERLIGHT	Optoelectronics	C	C1004	1	1,083	-	10 Bar Graph Display,25.3x10.1mm(1"x0.4"),Hi-Eff Red LED,GaAsP, 625nm,Gray,2.8mcd(Typ.)at 10mA(K Bin), in Tube Packing.
15	**ELB1001EWA(L)-EL-C**	EL, EVERLIGHT	Optoelectronics	C	C1004	2	2,204	-	10 Bar Graph Display,25.3x10.1mm(1"x0.4"),Hi-Eff Red LED,GaAsP, 625nm,Gray,2.8mcd(Typ.)at 10mA(L Bin), in Tube Packing.
16	**ELB1001EWA(M)-EL-C**	EL, EVERLIGHT	Optoelectronics	C	C1004	1	19	-	10 Bar Graph Display,25.3x10.1mm(1"x0.4"),Hi-Eff Red LED,GaAsP, 625nm,Gray,2.8mcd(Typ.)at 10mA(M Bin), in Tube Packing.
17	**ELB1001GWA(K)-EL-C**	EL, EVERLIGHT	Optoelectronics	C	C1004	3	190	-	10 Bar Graph Display,25.3x10.1mm(1"x0.4"),Green LED,Gap 570nm,Gray,3.0mcd(Typ.)at 10mA(K Bin), in Tube Packing

#	Part Number	Brand	Category	Package	Outline	Cartons	Quantity	Datasheet	Description
18	**ELB1001IDR-EL-C**	EL, EVERLIGHT	Optoelectronics	C	C1004	1	950	-	10 Bar Graph Display,25.3x10.1mm(1"x0.4"),Hi-Eff Red,GaAsP 625nm, 1.45mcd(Typ.)at 10mA, Red, in Tube Packing
19	**ELB1001YWA(K)-EL-C**	EL, EVERLIGHT	Optoelectronics	C	C1004	1	19	-	10 Bar Graph Display,25.3x10.1mm(1"x0.4"),Yellow LED,GaAsP, 590nm,Gray,1.5mcd(Typ.)at 10mA(K Bin), in Tube Packing
20	**ELB1001YWA(M)-EL-C**	EL, EVERLIGHT	Optoelectronics	C	C1004	1	703	-	10 Bar Graph Display,25.3x10.1mm(1"x0.4"),Yellow LED,GaAsP, 590nm,Gray,1.5mcd(Typ.)at 10mA(M Bin), in Tube Packing
21	**ELD316IDR(H)-EL-C**	EL, EVERLIGHT	Optoelectronics	C	D30H0	2	3,424	-	0.3" Dual Digit Displays,Hi-eff Red,GaAsP, 625nm,Red,1.8mcd(Typ.)at 10mA,Common Anode(H bin), in Tube Packing
22	**ELD316IDR(J)-EL-C**	EL, EVERLIGHT	Optoelectronics	C	D30H0	1	2,272	-	0.3" Dual Digit Displays,Hi-eff Red,GaAsP, 625nm,Red,1.8mcd(Typ.)at 10mA,Common Anode(J bin), in Tube Packing
23	**ELD316IDR(K)-EL-C**	EL, EVERLIGHT	Optoelectronics	C	D30H0	2	2,816	-	0.3" Dual Digit Displays,Hi-eff Red,GaAsP, 625nm,Red,1.8mcd(Typ.)at 10mA,Common Anode(K bin), in Tube Packing
24	**ELD316IDR(L)-EL-C**	EL, EVERLIGHT	Optoelectronics	C	D30H0	3	9,888	-	0.3" Dual Digit Displays,Hi-eff Red,GaAsP, 625nm,Red,1.8mcd(Typ.)at 10mA,Common Anode(L bin),in Tube Packing
25	**ELD316IDR(M)-EL-C**	EL, EVERLIGHT	Optoelectronics	C	D30H0	2	2,464	-	0.3" Dual Digit Displays,Hi-eff Red,GaAsP, 625nm,Red, 1.8mcd(Typ.)at 10mA,Common Anode(M bin),in Tube Packing
26	**ELD511HDB(G)-EL-C**	EL, EVERLIGHT	Optoelectronics	C	D56H8	2	1,120	-	0.56" Dual Digit Displays,Bright Red,GaP, 650nm,Red,0.4mcd(Typ.)at 10mA,Common Cathode(G Bin), in Tube Packing
27	**ELD511HDB(H)-EL-C**	EL, EVERLIGHT	Optoelectronics	C	D56H8	1	140	-	0.56" Dual Digit Displays,Bright Red,GaP, 650nm,Red,0.4mcd(Typ.)at 10mA,Common Cathode(H Bin), in Tube Packing
28	**ELD511IDR-EL-C**	EL, EVERLIGHT	Optoelectronics	C	D56H8	2	1,640	-	0.56" Dual Digit Displays,Hi-Eff Red,GaAsP, 625nm,Red,2.0mcd(Typ.)at 10mA,Common Cathode, in Bulk Packing
29	**ELF511EWA(J)X-EL-C**	EL, EVERLIGHT	Optoelectronics	C	Q56H2	1	70	-	0.56" Quadruple Digit Display,Hi-Eff Red,GaAsP/GaP,625nm,Gray,3.6mcd(Typ.)at 10mA,Commom Cathode(J Bin), in Tube Packing
30	**ELF511EWA(K)X-EL-C**	EL, EVERLIGHT	Optoelectronics	C	Q56H2	1	60	-	0.56" Quadruple Digit Display,Hi-Eff Red,GaAsP/GaP,625nm,Gray,3.6mcd(Typ.)at 10mA,Commom Cathode(K Bin), in Tube Packing
31	**ELF511EWA(L)X-EL-C**	EL, EVERLIGHT	Optoelectronics	C	Q56H2	2	780	-	0.56" Quadruple Digit Display,Hi-Eff Red,GaAsP/GaP,625nm,Gray,3.6mcd(Typ.)at 10mA,Commom Cathode(L Bin), in Tube Packing
32	**ELF511EWA(M)X-EL-C**	EL, EVERLIGHT	Optoelectronics	C	Q56H2	1	90	-	0.56" Quadruple Digit Display,Hi-Eff Red,GaAsP/GaP,625nm,Gray,3.6mcd(Typ.)at 10mA,Commom Cathode(M Bin), in Tube Packing
33	**ELM2001IDR(L)-EL-C**	EL, EVERLIGHT	Optoelectronics	C	C2115	1	182	-	2.0" 5*7 Dot Matrix Display,Hi-Eff Red,GaAsP,625nm,4.5mcd(Typ.)at 10mA,Red,Cathode Column, Anode Row(L Bin), in Tube Packing
34	**ELM2001IDR(M)-EL-C**	EL, EVERLIGHT	Optoelectronics	C	C2115	2	338	-	2.0" 5*7 Dot Matrix Display,Hi-Eff Red,GaAsP,625nm,4.5mcd(Typ.)at 10mA,Red,Cathode Column, Anode Row(M Bin), in Tube Packing
35	**ELS1002EWA(P)-EL-C**	EL, EVERLIGHT	Optoelectronics	C	S1RH4	2	990	-	1.0" Single Digit Display,Hi-Eff Red,GaAsP, 625nm,Gray,4.0mcd(Typ.)at 10mA,Common Anode(P Bin), in Tube Packing
36	**ELS2325IDR(N)-EL-C**	EL, EVERLIGHT	Optoelectronics	C	S230H0	1	70	-	2.3" Single Digit Display,Hi-eff Red,GaAsP, 625nm,Red,Common Cathode(N Bin), in Tube Packing
37	**ELS2325IDR(P)-EL-C**	EL, EVERLIGHT	Optoelectronics	C	S230H0	2	180	-	2.3" Single Digit Display,Hi-eff Red,GaAsP, 625nm,Red,Common Cathode(P Bin), in Tube Packing
38	**ELS2326SRDR(S)-EL-C**	EL, EVERLIGHT	Optoelectronics	C	S2R3H0	3	280	-	2.3" Single Digit Displays,Deep Hyper Red,GaAlAs,643nm,Red,11mcd(Typ.)at 10mA,Common Anode(S Bin), in Tube Packing
39	**ELS2326SRDR-EL-B**	EL, EVERLIGHT	Optoelectronics	B	S2R3H0	3	270	-	2.3" Single Digit Displays,Deep Hyper Red,GaAlAs,643nm,Red,11mcd(Typ.)at 10mA,Common Anode, in Bulk Packing
40	**ELS301HDB(G)-EL-C**	EL, EVERLIGHT	Optoelectronics	C	S30V0	1	832	-	0.3" Single Digit Display,Low Current Bright Red,GaP, 650nm,Black,0.3mcd(Typ.)at 10mA,Common Cathode(G Bin), in Tube Packing

#	Part Number	Brand	Category	Package	Outline	Cartons	Quantity	Datasheet	Description
41	**ELS315SRWA(M)-EL-C**	EL, EVERLIGHT	Optoelectronics	C	S36V0	1	105	-	0.36" Single Digit Display,Deep Hyper Red,GaAlAs 643nm,Gray,4.0mcd(Typ.)@10mA,Common Cathode
42	**ELS315SRWA(P)-EL-C**	EL, EVERLIGHT	Optoelectronics	C	S36V0	1	630	-	0.36" Single Digit Display,Deep Hyper Red,GaAlAs 643nm,Gray,4.0mcd(Typ.)at 10mA,Common Cathode,(P Bin), in Tube Packing.
43	**ELS315SRWA(Q)-EL-C**	EL, EVERLIGHT	Optoelectronics	C	S36V0	1	2,100	-	0.36" Single Digit Display,Deep Hyper Red,GaAlAs 643nm,Gray,4.0mcd(Typ.)at 10mA,Common Cathode,(Q Bin), in Tube Packing.
44	**ELS315SRWA(R)-EL-C**	EL, EVERLIGHT	Optoelectronics	C	S36V0	1	2,065	-	0.36" Single Digit Display,Deep Hyper Red,GaAlAs 643nm,Gray,4.0mcd(Typ.)at 10mA,Common Cathode,(R Bin), in Tube Packing.
45	**ELS321HDB(F)-EL-C**	EL, EVERLIGHT	Optoelectronics	C	S30V4	2	2,964	-	0.3" Single Digit Display,Low Current Bright Red,GaP, 650nm,Black, 0.3mcd(Typ.)at 10mA,Common Cathode,(F Bin), in Tube Packing
46	**ELS321RDB(D)-EL-C**	EL, EVERLIGHT	Optoelectronics	C	S30V4	2	104	-	0.3" Single Digit Display,Hyper Red,GaAsP, 645nm,Black, 0.5mcd(Typ.)at 10mA,Common Cathode(D Bin), in Tube Packing
47	**ELS321RDB(G)-EL-C**	EL, EVERLIGHT	Optoelectronics	C	S30V4	1	78	-	0.3" Single Digit Display,Hyper Red,GaAsP, 645nm,Black, 0.5mcd(Typ.)at 10mA,Common Cathode(G Bin), in Tube Packing
48	**ELS422EWA(H)-EL-C**	EL, EVERLIGHT	Optoelectronics	C	S43V4	1	52	-	0.43" Single Digit Display,Hi-eff Red,GaAsP, 625nm,Gray,1.7mcd(Typ.)at 10mA,Common Anode(H Bin), in Tube Packing
49	**ELS422EWA(J)-EL-C**	EL, EVERLIGHT	Optoelectronics	C	S43V4	2	2,002	-	0.43" Single Digit Display,Hi-eff Red,GaAsP, 625nm,Gray,1.7mcd(Typ.)at 10mA,Common Anode(J Bin), in Tube Packing
50	**ELS422EWA(K)-EL-C**	EL, EVERLIGHT	Optoelectronics	C	S43V4	2	910	-	0.43" Single Digit Display,Hi-eff Red,GaAsP, 625nm,Gray,1.7mcd(Typ.)at 10mA,Common Anode(K Bin), in Tube Packing
51	**ELS422HWB(E)-EL-C**	EL, EVERLIGHT	Optoelectronics	C	S43V4	1	1,352	-	0.43" Single Digit Display,Low Current Bright Red,GaP, 650nm,Black,0.5mcd(Typ.)at 10mA,Common Anode(E Bin), in Tube Packing
52	**ELS511HDB(F)-EL-C**	EL, EVERLIGHT	Optoelectronics	C	S56H0	1	560	-	0.56" Single Digit Display, Bright Red, Gap 650nm,Black,0.36mcd(Typ.)at 10mA,Common Cathode(F Bin), in Tube Packing
53	**ELS511HDB(G)-EL-C**	EL, EVERLIGHT	Optoelectronics	C	S56H0	1	680	-	0.56" Single Digit Display, Bright Red, Gap 650nm,Black,0.36mcd(Typ.)at 10mA,Common Cathode(G Bin), in Tube Packing
54	**ELS511IDR(G)-EL-C**	EL, EVERLIGHT	Optoelectronics	C	S56H0	1	40	-	0.56" Single Digit Display,Hi-eff Red,GaAsP 625nm,Red,0.8mcd(Typ.)at 10mA,Common Cathode(G Bin), in Tube Packing
55	**ELS511IDR(J)-EL-C**	EL, EVERLIGHT	Optoelectronics	C	S56H0	1	720	-	0.56" Single Digit Display,Hi-eff Red,GaAsP 625nm,Red,0.8mcd(Typ.)at 10mA,Common Cathode(J Bin),in Tube Packing
56	**ELS511IDR(K)-EL-C**	EL, EVERLIGHT	Optoelectronics	C	S56H0	4	6,880	-	0.56" Single Digit Display,Hi-eff Red,GaAsP 625nm,Red,0.8mcd(Typ.)at 10mA,Common Cathode(K Bin),in Tube Packing
57	**ELS511IDR(L)-EL-C**	EL, EVERLIGHT	Optoelectronics	C	S56H0	3	320	-	0.56" Single Digit Display,Hi-eff Red,GaAsP 625nm,Red,0.8mcd(Typ.)at 10mA,Common Cathode(L Bin),in Tube Packing
58	**ELS511IDR(M)-EL-C**	EL, EVERLIGHT	Optoelectronics	C	S56H0	1	200	-	0.56" Single Digit Display,Hi-eff Red,GaAsP 625nm,Red,0.8mcd(Typ.)at 10mA,Common Cathode(M Bin), in Tube Packing
59	**ELS511IDR(N)-EL-C**	EL, EVERLIGHT	Optoelectronics	C	S56H0	1	40	-	0.56" Single Digit Display,Hi-eff Red,GaAsP 625nm,Red,0.8mcd(Typ.)at 10mA,Common Cathode(N Bin), in Tube Packing
60	**ELS512GWA(L)-EL-C**	EL, EVERLIGHT	Optoelectronics	C	S56H0	1	520	-	0.56" Single Digit Display,Green ,GaP 570nm,Gray,3.40mcd(Typ.)at 10mA,Common Anode(L Bin), in Tube Packing
61	**ELS512GWA(M)-EL-C**	EL, EVERLIGHT	Optoelectronics	C	S56H0	2	2,120	-	0.56" Single Digit Display,Green ,GaP 570nm,Gray,3.40mcd(Typ.)at 10mA,Common Anode(M Bin), in Tube Packing
62	**ELS515GWA(K)-EL-C**	EL, EVERLIGHT	Optoelectronics	C	S52H0	1	40	-	0.52" Single Digit Display,Green,GaP 570nm,Gray,6.3mcd(Typ.)at 10mA,Common Cathode(K Bin), in Tube Packing
63	**ELS515GWA-EL-TU**	EL, EVERLIGHT	Optoelectronics	TU	S52H0	1	3,520	-	0.52" Single Digit Display,Green,GaP,570nm,Gray,6.3mcd(Typ.)at 10mA,Common Cathode, in Tube Packing, RoHS
64	**ELS516EWA(L)-EL-C**	EL, EVERLIGHT	Optoelectronics	C	S52H0	1	800	-	0.52" Single Digit Display,Hi-Eff Red,GaAsP,625nm,Gray,3.2mcd(Typ.)at 10mA,Common Anode(L Bin), in Tube Packing

#	Part Number	Brand	Category	Package	Outline	Cartons	Quantity	Datasheet	Description
65	**ELS516EWA(M)-EL-C**	EL, EVERLIGHT	Optoelectronics	C	S52H0	1	160	-	0.52" Single Digit Display,Hi-Eff Red,GaAsP,625nm,Gray,3.2mcd(Typ.)at 10mA,Common Anode(M Bin), in Tube Packing
66	**ELS516EWA(N)-EL-C**	EL, EVERLIGHT	Optoelectronics	C	S52H0	1	80	-	0.52" Single Digit Display,Hi-Eff Red,GaAsP,625nm,Gray,3.2mcd(Typ.)at 10mA,Common Anode(N Bin), in Tube Packing
67	**FND317C-QT-C**	QT	Optoelectronics	C	S36V0	1	25	-	0.362 INCH RED 7 SEGMENT DISPL
68	**GMC2975C-QT-C**	QT	Optoelectronics	C	C2115	1	40	-	2.0 INCH RED/GREEN/YELLOW/RED-
69	**GMC7175CA-QT-C**	QT	Optoelectronics	C	C0705	1	28	-	0.70 INCH RED/GREEN/YELLOW DOT
70	**H11AA3-QT-C**	QT	Optoelectronics	C	DIP-6	1	50	H11AA3	Optocouplers/TR Output/AC Input, CTR>=50%, Vceo>=30V, Vce(Sat)<=0.4V, Iceo<=50nA, Viso>=5300VAC(rms), 1 min, in DIP-6 package
71	**H11B255-QT-C**	QT	Optoelectronics	C	DIP-6	1	900	H11B255	Optocouplers/Darlington Output, CTR >=100%, Vceo >=55V, Viso >=5300Vrms, Vce(Sat) <=1.0V, in DIP-6
72	**H11C5-QT-C**	QT	Optoelectronics	C	DIP-6	1	50	-	Photocoupler/SCR output, IFT<=20MA at 50V, VDM>=400V, in DIP-6
73	**H11D1-QT-C**	QT	Optoelectronics	C	DIP-6	2	450	H11D1	High Voltage Optocouplers/TR Output/GaAs Input, CTR >=20%, Vceo >=300V, Viso >=5300Vrms, Vce(Sat) <=0.4V, in DIP-6
74	**H11D4.300-QT-C**	QT	Optoelectronics	C	DIP-6	1	1,000	H11D4.300	High Voltage Optocouplers/TR Output/GaAs Input-VDE0884, CTR >=10%, Vceo >=200V, Viso >=5300Vrms, Vce(Sat) <=0.4V, in DIP-6
75	**H11F3-QT-C**	QT	Optoelectronics	C	DIP-6	1	50	-	Photocoupler, FET Output, BV>=15V, RDSON<=470 OHMS, in Dip-6 Package
76	**H11G2-QT-C**	QT	Optoelectronics	C	DIP-6	2	11,800	H11G2	High Voltage Optocouplers/Darlington Output/GaAs Input, CTR >=1000%, Vceo >=80V, Viso >=5300Vrms, Vce(Sat) <=1.0V, in DIP-6
77	**H11G2.300-QT-C**	QT	Optoelectronics	C	DIP-6	1	850	H11G2.300	High Voltage Optocouplers/Darlington Output/GaAs Input-VDE0884, CTR >=100%, Vceo >=80V, Viso >=5300Vrms, Vce(Sat) <=1.0V, in DIP-6
78	**H11G3-QT-C**	QT	Optoelectronics	C	DIP-6	2	1,250	H11G3	High Voltage Optocouplers/Darlington Output/GaAs Input, CTR >=200%, Vceo >=55V, Viso >=5300Vrms, Vce(Sat) <=1.2V, in DIP-6
79	**HCPL-2601-QT-C**	QT	Optoelectronics	C	DIP-8	1	3,300	HCPL-2601	Optocouplers/Very High Speed Logic Gate Output, Viso >=2500Vrms, Typical Data Rate=10Mbit/s, Output Current TTL-loads=8.0, Propogation Delay Time Tphl=0.075ns,Tplh=0.075ns, in DIP-8
80	**HCPL-2631-QT-C**	QT	Optoelectronics	C	DIP-8	1	5,500	HCPL-2631	Optocouplers/Very High Speed Logic Gate Output/AlGaAs-GaAsP Input, Viso >=2250Vrms, Ift=5.0mA,Vcc=5.5V,Vol=0.6V, Typical Tphl=0.075us,Tplh=0.075us, in DIP-8
81	**HCPL-2730-QT-C**	QT	Optoelectronics	C	DIP-8	1	4,700	HCPL-2730	Optocouplers/Dual Split Darlington Output/AlGaAs Input, Viso >=2500Vrms, Ift=1.6mA,Vcc=7.0V,Vol=0.4V, Typical Tphl=20us,Tplh=35+us, in DIP-8
82	**HLMP-2655-QT-C**	QT	Optoelectronics	C	C0404	1	150	-	8 Pin In-Line Light Bar (0.35" x 0.35"), GaAsP Red, Hi-Eff 630nm, White Diffused, typ. 43mcd(If=20mA), typ. 50mcd(If=60mA)
83	**HLMP-2885-QT-C**	QT	Optoelectronics	C	C0804	2	125	-	16 Pin In-Line Light Bar (0.35" x 0.70"), GaP Green 565nm, Color Diffused, typ. 50mcd(If=20mA), typ. 75mcd(If=60mA)
84	**HLMP-3850A-QT-B**	QT	Optoelectronics	B	R5	2	40,000	-	5mm(T-1 3/4) Round,Cut Flange with Stopper,Yellow LED,PL=585nm,150mcd(Typ)at 20mA, 24 Degree,in Bulk Packing
85	**MAN4610A-QT-C**	QT	Optoelectronics	C	S40V4	1	25	-	0.4" Single Digit Display,Reddish Orange,GaAsP 630nm,Color Diffused,1800ucd(Typ.)@10mA,Orange,Common Anode
86	**MAN4740A-QT-C**	QT	Optoelectronics	C	S40V4	1	25	-	0.4" Single Digit Display,Hyper Red,GaAsP 660nm,Color Diffused,350ucd(Typ.)@10mA,Black,Common Cathode
87	**MAN5350-QT-C**	QT	Optoelectronics	C	S51H0	1	240	-	0.51" Single Digit Display,Yellow,GaAsP 585nm,White Diffused,1200ucd(Typ.)@10mA,Gray,Common Anode
88	**MAN5450-QT-C**	QT	Optoelectronics	C	S51H0	1	40	-	0.51" Single Digit Display,Green,GaAsP 565nm,White Diffused,3000ucd(Typ.)@10mA,Gray,Common Anode
89	**MAN6950-QT-C**	QT	Optoelectronics	C	K56H8	1	120	-	0.56" Digit +/-1.8 Display,Hi-Eff Red,GaAsP 635nm(Peak Wavelength),Red,2200ucd(Typ.)@10mA,Common Cathode
90	**MAN8240-QT-C**	QT	Optoelectronics	C	S80V4	1	20	-	0.8" Single Digit Display,Deep Hyper Red,GaAlAs 660nm,Color Diffused,3500ucd(Typ.)@5mA,Gray,Common Cathnode

#	Part Number	Brand	Category	Package	Outline	Cartons	Quantity	Datasheet	Description
91	**MCT2-QT-C**	QT	Optoelectronics	C	DIP-6	1	50	MCT2	Optocouplers/TR Output, CTR >=20%, Vceo >=30V, Viso >=5300Vrms, Vce(Sat) <=0.4V, in DIP-6
92	**MCT210-QT-C**	QT	Optoelectronics	C	DIP-6	2	100	MCT210	Optocouplers/TR Output, CTR >=150%, Vceo >=30V, Viso >=5300Vrms, Vce(Sat) <=0.4V, in DIP-6
93	**MCT271-QT-C**	QT	Optoelectronics	C	DIP-6	1	150	MCT271	Optocouplers/TR Output, CTR 45~90%, Vceo >=30V, Viso >=5300Vrms, Vce(Sat) <=0.4V, Typical ton=7.0us,toff=7.0us, in DIP-6
94	**MCT2E-QT-C**	QT	Optoelectronics	C	DIP-6	1	100	MCT2E	Optocouplers/TR Output, CTR >=20%, Vceo >=30V, Viso >=5300Vrms, Vce(Sat) <=0.4V, in DIP-6
95	**MCT5211-QT-C**	QT	Optoelectronics	C	DIP-6	1	2,000	MCT5211	Optocouplers/TR Output/AlGaAs Input, CTR >=150%, Vceo >=30V, Viso >=5300Vrms, Vce(Sat) <=0.4V, in DIP-6
96	**MOC3021-QT-C**	QT	Optoelectronics	C	DIP-6	1	150	-	Optocoupler -Traic Output (240VAC), Ift<=15mA, Vdrm=400V, Idrm<=100nA, Itsm=1A@1ms, Vtm<=3V, Ih(typ)=100uA, Viso >7500VAC(pk) in DIP-6
97	**MOC8111-QT-C**	QT	Optoelectronics	C	DIP-6	1	1,200	MOC8111	Optocouplers/TR Output/GaAs Input, CTR >=20%, Vceo >=30V, Viso >=5300Vrms, Vce(Sat) <=0.4V, Typical ton=10us, toff=10us, in DIP-6
98	**MV5055-QT-B**	QT	Optoelectronics	B	R5	1	500	-	5mm (T-1 3/4) Round , Cut Flange, Red LED, GaAsP, 660nm, 0.3mcd(Tpy.) at 20mA, Color Diffused, 150 degree Viewing Angle, in Bulk Packing
99	**MV5491A-QT-B**	QT	Optoelectronics	B	R5	3	13,250	-	5mm(T-1 3/4) Round, Cut Flange,2-lead, Red LED, GaAlAs, 650nm, Green LED, GaP, 568nm, 6mcd(Tpy.) at 20mA, White Diffused,100 Degree, with Stopper, Green Cathode, in Bulk Packing.
100	**MV57164-QT-C**	QT	Optoelectronics	C	C1004	1	360	-	10 Bar Graph Display, GaAsP Red, Hi-Eff 630nm, Gray, typ. 510mcd(If=10mA),
101	**MV5753-QT-B**	QT	Optoelectronics	B	R5	1	20,000	-	5mm (T-1 3/4) Round, Cut Flange, Deep Red LED, GaAsP, 635nm, 15mcd (Tpy.) at 20mA, Color Diffused, 65 degree Viewing Angle, in Bulk Packing
102	**MV6353-QT-B**	QT	Optoelectronics	B	R5	1	10,000	-	5mm (T-1 3/4) Round, Cut Flange, Super Yellow LED, GaAsP, 585nm, 15mcd(Tpy.) at 20mA, Color Diffused, 65 degree Viewing Angle, in Bulk Packing
103	**MV8103-QT-B**	QT	Optoelectronics	B	R5	1	1,500	-	5mm (T-1 3/4) Round , Cut Flange, Red LED, GaAsP, 660nm, 940mcd(Tpy.) at 20mA, Water Clear, 20 degree Viewing Angle, in Bulk Packing
104	**TLN-G3R5-3525-QT-B**	QT	Optoelectronics	B	R5	1	750	-	5mm (T-1 3/4) Round , Cut Flange, Green LED, GaP, 565nm, 25mcd(Tpy.) at 20mA, Color Tinted, 35 degree Viewing Angle, in Bulk Packing

Terms of Sale

All sales are final. Products are sold as-is, as complete pallet lots, with no returns. Bids are based on ex-warehouse terms. The buyer is responsible for freight, pickup, export/import requirements, taxes, duties, and applicable handling or compliance costs. Availability is subject to prior sale, bid acceptance, and final confirmation by Taitron Components.